SAFETY DATA SHEET



Date Issued: 06/23/2015

SDS No: 8504

Date Revised: 03/01/2020 Revision No: 1

C KLEAR 421

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: C KLEAR 421

GENERAL USE: Windshield Washer Concentrate

PRODUCT CODE: 8504

MANUFACTURER

John-Henry Enterprises, Inc. 2813 Richland Ave Metairie, LA 70002

Emergency Contact: H. Zeller Emergency Phone: 504-888-8989

24 HR. EMERGENCY TELEPHONE NUMBERS

US/Canada: 800-535-5053

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Eye Irritation, Category 2 Skin Irritation, Category 4

Physical:

Flammable Liquids, Category 1A

GHS LABEL

FLAMMABLE LIQUID and VAPOR. Keep away from flame and other sources of ignition.

WARNING: Skin and eye irritant. Vapors may cause dizziness, drowsiness, CNS depression, and irritation to nose, throat, and respiratory system.



Irritant



Flammable Liquid

SIGNAL WORD: DANGER HAZARD STATEMENTS

H320: Causes eye irritation. H316: Causes mild skin irritation. H226: Flammable liquid and vapour.

H302 + H332: Harmful if swallowed or if inhaled.

H336: May cause drowsiness or dizziness.

PRECAUTIONARY STATEMENTS

General:

P102: Keep out of reach of children.

P103: Read label before use.

Prevention:

2828VC61: Avoid eye contact

P270: Do not eat, drink or smoke when using this product.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Storage:

75990X3S: Keep only in original container. Store in a cool, well-ventilated space. Keep container tightly closed.

EMERGENCY OVERVIEW

IMMEDIATE CONCERNS: Vapors can cause nausea, dizziness, nausea, stupor, vomiting, headache, and/or irritation to nose, throat, and respiratory system. Causes irritation to eyes. Prolonged exposure may irritate skin.

POTENTIAL HEALTH EFFECTS

EYES: May cause moderate irritation including stinging, burning, tearing, redness, and temporary blurring of vision.

SKIN: Prolonged or repeated exposure may cause dryness, defatting, redness, rash, irritation, sensitization and/or dermatitis.

INGESTION: Causes irritation to mouth, throat, esophagus, and gastrointestinal system .May cause gastrointestinal disconfort, including nausea, vomiting, diarrhea, etc. May be harmful or fatal if swallowed.

INHALATION: Mists, sprays, or vapor can be irritating to eyes and respiratory tract. Vapors and mists can cause irritation, dizziness, drowsiness, headache, and other central nervous system depression

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Alcohol	15 - 20	Proprietary
Other ingredients are not hazardous or are present at levels that do not present a significant hazard.	>80	mixture

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for 15 minutes or until dscomfort eases. Get medical attention if irritation persists.

SKIN: Remove contaminated clothing and footwear. Wash with soap and water. Get medical attention if irritation develops or persists.

INGESTION: Get immediate medical attention (call 911). Keep patient warm, calm, and quiet. Rinse mouth with water. DO NOT induce vomiting unless instructed to do so by poison center or physician.

INHALATION: If affected by vapors, spray or mist, move to fresh air. Seek medical attention if symptoms persist or worsen. Give oxygen if breathing is difficult and seek prompt medical attention.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Moderate irritation, stinging, burning, temporary blurring of vision

SKIN: Prolonged or repeated contact may produce mild irritation, including redness, burining or itching, rash, etc.

INGESTION: Harmful or fatal if swallowed. Causes irritation to mouth, throat, esophagus, and GI tract. Can cause gastrointestinal discomfort, including nausea, vomiting, and diarrhea.

INHALATION: Vapors, spray or mists can irritate eyes, nose, throat, and respiratory tract. Vapors can cause dizziness, drowsiness, nausea, headache, drunkenness, vomiting, unconsciousness, and other anesthetic effects.

NOTES TO PHYSICIAN: Treat symptomatically.

5. FIRE FIGHTING MEASURES

FLAMMABLE CLASS: GHS Category - 2; OSHA, US DOT - Flammable liquid

GENERAL HAZARD: Flammable liquid and vapor. Vapors are heavier than air and may travel to remote ignition sources and be ignited.

EXTINGUISHING MEDIA: Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon and hydrocarbon residues.

EXPLOSION HAZARDS: Containers can burst if exposed to flames or high temperatures. Vapors are heavier than air and can propagate to remote areas and be ignited.

FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus when fighting chemical fires. Use water fog or spray to cool containers and/or disperse product vapors.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Wear recommended PPE. Ventilate the area and remove uninvolved personnell. Extinguish nearby sources of ignition. Contain and absorb spilled material. Dispose of contaminated absorbant properly. Wash spill area with soap and water.

LARGE SPILL: Wear appropriate PPE. Stop flow. Ventilate the area and extinguish nearby sources of ignition. Remove uninvolved personnel from area. Contain spill and keep from entering sewer or surface waterways. Collect spill into suitable, properly labeled containers for use or disposal. Wash spill area with water or detergent solution.

7. HANDLING AND STORAGE

HANDLING: Avoid contact with eyes. Read and understand label and SDS before handling any chemical. Use only in well ventilated areas away from ignition sources. Ground and bond containers when pouring or transfering to another container. Open drums slowly to release accumulated pressure.

STORAGE: Store in original containers in a cool, well ventilated area away from heat, sparks, flame or other sources of ignition. Keep containers tightly closed when not in use.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)							
	EXPOSURE LIMITS						
Chemical Name	Туре		ppm	mg/m³			
Alcohol	OSHA PEL	TWA	400	980			
	ACGIH TLV	TWA	200	490			
		STEL	400	960			

ENGINEERING CONTROLS: Maintain sufficient ventilation in storage and use areas to prevent the accumulation of product vapors, fumes, spray, or mists. Provide local exhaust for enclosed areas.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Avoid eye contact. Wear safety glasses or goggles

SKIN: Avoid prolonged or repeated contact. Wear rubber, latex, or other chemical resistant gloves.

RESPIRATORY: Use with adequate ventilation. Wear a NIOSH approved air purifying respirator where vapors, mists or spray are excessive or exceed exposure limits.

WORK HYGIENIC PRACTICES: Wash thoroughly before eating, drinking, smoking, or using the facilities after handling any chemical product.

OTHER USE PRECAUTIONS: Working eyewash stations and safety showers should be located in or near all areas where chemicals are stored or used.

9. PHYSICAL AND CHEMICAL PROPERTIES

ODOR: strong, alcohol

APPEARANCE: clear, blue liquid

pH: 7.0 to 8.0 **Notes:** as made

PERCENT VOLATILE: greater than 99% **FLASH POINT AND METHOD:** < (60°F)

FLAMMABLE LIMITS: 2% (alcohol) to 12.7 (alcohol)

VAPOR PRESSURE: Not determined VAPOR DENSITY: Heavier than air BOILING POINT: 180 - 210 deg F

FREEZING POINT: less than 32 deg F (0 deg C)
SOLUBILITY IN WATER: Complete in all proportions.

SPECIFIC GRAVITY: 0.98 to 1.00

(VOC): ~ 18 percent (w/w)

10. STABILITY AND REACTIVITY

REACTIVITY: No

HAZARDOUS POLYMERIZATION: No

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon and hydrocarbon residues, acrid fumes

INCOMPATIBLE MATERIALS: oxidizing agents.

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

NOTES: No toxicity data available for product

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: No data

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Ship to a solvent reclaimation facility or chemical incenerator. Liquid wastes cannot be landfilled. Follow all pertinent local, state, and Federal disposal regulations.

FOR LARGE SPILLS: See Section 6

EMPTY CONTAINER: Triple rinse container thoroughly with water and recycle.

RCRA/EPA WASTE INFORMATION: Unused or undiluted product would constitute an RCRA regulated hazardous waste due to Ignitability

(Hazardous Waste Code: D001; Flashpoint less than 140 deg F)

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: UN1993, Flammable Liquid, n.o.s. (contains 2-propanol), 3, III

VESSEL (IMO/IMDG)

SHIPPING NAME: UN 1993, FLAMMABLE LIQUID, N.O.S. (contains 2-propanol), 3, PG III

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HEALTH HAZARDS: Flammable liquid and vapor; Acute health hazard (eye and skin irritation); Acute inhalation hazard

EPCRA SECTION 313 SUPPLIER NOTIFICATION

Chemical Name	Wt.%	CAS
Alcohol	15 - 20	Proprietary

TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
Alcohol	Proprietary

TSCA STATUS: All other ingredients are included on the TSCA Inventory or are exempt

CALIFORNIA PROPOSITION 65: Contains no substances known to the State of California to cause cancer, birth defects, or reproductive harm.

16. OTHER INFORMATION

APPROVED BY: H. Zeller


PREPARED BY: CSCC Date Revised: 03/01/2020

REVISION SUMMARY: This SDS replaces the 06/24/2015 SDS. Revised: Section 1: REASON FOR ISSUE.

HMIS RATING



NFPA CODES



GENERAL STATEMENTS: Amounts given herein (other than for regulatory purposes) are typical and do not represent a specification. Unspecified or unlisted components are proprietary, do not present a hazard at levels present, are not hazardous, and/or are present It levels below reportable limits. Exact percentage values for all components are proprietary in accordance with 29 CFR 1910.1200(i)

MANUFACTURER DISCLAIMER: To the best of our knowledge, the information contained herein is accurate. However, no liability whatsoever is assumed for its accuracy and/or completeness. Final determination of the suitability of any material is the sole responsibility of the user. All materials may present unknown health or physical hazards and should be used with caution. Certain hazards are described herein, but no guarantee is made that these are the only hazards associated with the material that exist.