

SAFETY DATA SHEET



Date Issued : 07/08/2015
 SDS No : 5422
 Date Revised : 03/01/2020
 Revision No : 1

FORMULA 319

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: FORMULA 319
GENERAL USE: Stainless Steel Passivation Solution
PRODUCT CODE: 5422

MANUFACTURER

John-Henry Enterprises, Inc.
 2813 Richland Ave
 Metairie, LA 70002
Emergency Contact: H. Zeller
Emergency Phone: 504-888-8989

24 HR. EMERGENCY TELEPHONE NUMBERS

US/Canada: 800-535-5053

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS**Health:**

Eye Irritation, Category 2A
 Skin Irritation, Category 3

GHS LABEL

Causes moderate to severe irritation to eyes. Prolonged exposure can cause moderate to severe irritation to skin. Mists and spray can irritate eyes, nose, throat, and respiratory system.



Irritant

SIGNAL WORD: WARNING

HAZARD STATEMENTS

H315: Causes skin irritation.
 H320: Causes eye irritation.

PRECAUTIONARY STATEMENTS**General:**

P102: Keep out of reach of children.
 P103: Read label before use.

Prevention:

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.
 2828VC61: Avoid eye contact

Response:

P353: Rinse skin with water [or shower].
 P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Storage:

75990X3S: Keep only in original container. Store in a cool, well-ventilated space. Keep container tightly closed.

POTENTIAL HEALTH EFFECTS

EYES: Severely irritating and may cause temporary blurring of vision and temporary damage

SKIN: Prolonged contact may cause severe skin irritation and possible burns.

INGESTION: Causes irritation to mouth, throat, esophagus, and gastrointestinal system .May cause gastrointestinal discomfort, including nausea, vomiting, diarrhea, etc

INHALATION: Mists, sprays, or vapor can be irritating to eyes and respiratory tract.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Organic Acid	45 - 50	77-92-9

4. FIRST AID MEASURES

EYES: Gently hold eyelids open and flush with water for 15 minutes or until discomfort eases. Remove contact lenses if possible. Seek medical attention if irritation persists or vision remains blurred.

SKIN: Remove contaminated clothing and footwear. Flush off with water. Get medical attention if irritation develops or persists.

INGESTION: Get immediate medical attention (call 911). Rinse mouth with water. Do not induce vomiting unless instructed to do so by poison center or physician. Give patient water and milk of magnesia or other antacid tablets unless unconscious or convulsing. Keep patient warm and comfortable. Treat for shock.

INHALATION: If affected by vapors, spray or mist, move to fresh air. Seek medical attention if symptoms persist or worsen.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Moderate to severe irritation, including copious tearing, stinging, burning, temporary blurring of vision

SKIN: Prolonged or repeated contact may produce irritation, redness, edema, burning or itching, rash, etc.

INGESTION: Causes irritation to mouth, throat, esophagus, and GI tract. Can cause gastrointestinal discomfort, including nausea, vomiting, and diarrhea.

INHALATION: Spray or mists can irritate eyes, nose, throat, and respiratory tract.

5. FIRE FIGHTING MEASURES

FLAMMABLE CLASS: Not Applicable - Water based product with no flashpoint.

EXTINGUISHING MEDIA: Not applicable - water based product. After water has evaporated, use water (fog or spray) or chemical foam on burning solids.

HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon and hydrocarbon residues.

EXPLOSION HAZARDS: Containers can burst if exposed to flames or high temperatures.

FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus when fighting chemical fires. Use water fog or spray to cool intact containers.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Wear recommended PPE. Collect spilled product for reuse or disposal. Rinse spill area with water

LARGE SPILL: Wear appropriate PPE. Remove uninvolved personnel from area. Stop flow. Contain spill and keep from entering sewer or surface waterways. Collect spill into suitable, properly labeled containers for use or disposal. Rinse spill area with water.

7. HANDLING AND STORAGE

HANDLING: Avoid contact with eyes and prolonged contact with skin. Avoid prolonged exposure to mists and sprays. Read and understand product label and SDS before handling any chemical. Always wear recommended personal protective equipment. Follow label cautions and instructions.

STORAGE: Store in original containers in well ventilated area. Keep containers closed when not in use.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Wear safety glasses or goggles and face shield (recommended) when handling.

SKIN: Wear rubber, latex, or other chemical resistant gauntlet gloves and boots

WORK HYGIENIC PRACTICES: Wash thoroughly before eating, drinking, smoking, or using the facilities after handling any chemical product.

OTHER USE PRECAUTIONS: Working eyewash stations and safety showers should be located in or near all areas where chemicals are stored or used.

9. PHYSICAL AND CHEMICAL PROPERTIES

ODOR: mild

APPEARANCE: clear, colorless liquid

pH: 2.0 to 3.0

Notes: (5% in water)

PERCENT VOLATILE: 50 - 55% (w/w)

FLASH POINT AND METHOD: No flashpoint

VAPOR PRESSURE: Same as water (approximately)

VAPOR DENSITY: Same as water (approximately)

BOILING POINT: greater than 212 deg F

FREEZING POINT: less than 32 deg F (0 deg C)

SOLUBILITY IN WATER: Complete in all proportions.

EVAPORATION RATE: Same as water (approximately)

SPECIFIC GRAVITY: 1.25 to 1.27

10. STABILITY AND REACTIVITY

REACTIVITY: Reactive with alkaline materials.

HAZARDOUS POLYMERIZATION: No

STABILITY: Stable under recommended storage conditions

POSSIBILITY OF HAZARDOUS REACTIONS: Reacts with concentrated alkalis (generating heat and steam) and with concentrated oxidizing agents. Severity of reactions is concentration dependent.

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of carbon and hydrocarbon residues

INCOMPATIBLE MATERIALS: Strong alkalis (bases), chlorine bleach, oxidizing and reducing agents

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

NOTES: No toxicity data available for product

12. ECOLOGICAL INFORMATION

AQUATIC TOXICITY (ACUTE): Daphnia magna - 1535 mg/l (24 hr)

48-HOUR EC₅₀: 440 mg/l (leuciscus idus melanolus)

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Unused or undiluted product constitutes a hazardous waste. Follow all appropriate local, state, and Federal disposal regulations. Collect and neutralize spent solutions and discharge to a waste water treatment facility.

FOR LARGE SPILLS: See Section 6

EMPTY CONTAINER: Triple rinse container thoroughly with water and recycle.

RCRA HAZARD CLASS: D002 - Corrosive (pH less than 2.5)

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: NOT REGULATED

VESSEL (IMO/IMDG)

SHIPPING NAME: NOT REGULATED

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HEALTH HAZARDS: Acute health hazard (eye and skin irritation)


TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
Organic Acid	77-92-9

CALIFORNIA PROPOSITION 65: Contains no substances known to the State of California to cause cancer, birth defects, or reproductive harm.

16. OTHER INFORMATION**APPROVED BY:** H. Zeller**PREPARED BY:** CSCC **Date Revised:** 03/01/2020**REVISION SUMMARY:** This SDS replaces the 07/08/2015 SDS. Revised: **Section 1:** REASON FOR ISSUE.**HMIS RATING**

HEALTH	<input type="checkbox"/>	3
FLAMMABILITY	<input type="checkbox"/>	1
PHYSICAL HAZARD	<input type="checkbox"/>	0
PERSONAL PROTECTION	<input checked="" type="checkbox"/>	

NFPA CODES

GENERAL STATEMENTS: Amounts given herein (other than for regulatory purposes) are typical and do not represent a specification. Unspecified or unlisted components are proprietary, do not present a hazard at levels present, are not hazardous, and/or are present at levels below reportable limits. Exact percentage values for all components are proprietary in accordance with 29 CFR 1910.1200(i)

MANUFACTURER DISCLAIMER: To the best of our knowledge, the information contained herein is accurate. However, no liability whatsoever is assumed for its accuracy and/or completeness. Final determination of the suitability of any material is the sole responsibility of the user. All materials may present unknown health or physical hazards and should be used with caution. Certain hazards are described herein, but no guarantee is made that these are the only hazards associated with the material that exist.