

# RESTORE

## RUST CONVERTER & PROTECTIVE COATING

### DESCRIPTION

RESTORE stops further erosion and rusting of machinery, tools, vehicles, equipment, boats, metal buildings and more. When painted on, RESTORE chemically converts rust into a black organic complex. A clear acrylic coating is formed. The coating is sufficient to last for years without painting, or it can be painted over using latex, oil based or epoxy paint. Extends the life of anything made of metal.

### APPLICATIONS

For use by industrial plants, schools, institutions, office buildings, homes, farms and shipyards. Formulated for automobiles, boats, heavy equipment, metal buildings, tools and railroads.

### FEATURES & BENEFITS

- Oxidizes corrosion and scale
- Brightens surfaces
- Highly concentrated and powerful

### SPECIFICATIONS

**FORM:** Water-Based Liquid  
**ODOR:** Solvent  
**COLOR:** Milky White  
**DETERGENCY:** N/A  
**TOXICITY:** Non-hazardous  
**WETTING ABILITY:** Excellent  
**STORAGE STABILITY:** 1 Year +  
**COLD STABILITY:** 35°F  
**% VOC:** 2%

**FLASH POINT:** N/A  
**BOILING POINT:** >212°F  
**SOLUBILITY IN WATER:** 100%  
**SPECIFIC GRAVITY:** 1.025  
**% VOLATILE BY VOLUME:** 60%  
**pH:** <2  
**VISCOSITY:** Thick  
**EVAPORATION RATE:** Slow  
**BIODEGRADABILITY:** No

### LABEL INFORMATION

#### RESTORE RUST CONVERTER & PROTECTIVE COATING

RESTORE stops further erosion and rusting of machinery, tools, vehicles, equipment, boats, metal buildings, and more. When painted on, Restore chemically converts rust into a black organic complex. A clear acrylic coating is formed. The coating is sufficient to last for years without painting, or it can be painted over using latex, oil based or epoxy paint. Extends life of anything made of metal.


**DIRECTIONS:** Shake well. Clean rusted surface of loose rust flakes with wire brush. Apply product at the rate of 300 to 500 sq. ft. per gallon. Apply by brushing, dipping, swabbing or spraying product evenly over rusted surface. May be applied using equipment designed to spray latex paint. If necessary, when spraying add up to 3 oz. of water per gallon. Allow to dry completely. A clear hard finish will form. Surface may be painted or left as is after drying. Do not store at 32°F or below.

**WARNING:** Causes eye irritation.

Wash hands thoroughly after handling. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

**CONTAINS (CAS):** Water (7732-18-5), Aqueous Polystyrene-/Acrylic Emulsion Polymer (N/A), Tannic Acid (1401-55-4), 2-Butoxyethanol (111-76-2).

HEALTH	1
FLAMMABILITY	0
REACTIVITY	0
PERSONAL	B



### PACKAGING INFORMATION

Available in 12 x 1 quarts, 4 x 1 gallons, 5 and 6 gallon pails, and 55 gallon drums.