




ATR-165

Tar & Adhesive Remover

Product Description



ATR-165 is specifically compounded to quickly clean vehicles and equipment exposed to tar, asphalt, bitumen, oil, grease, sludge and asphalt-based plastic cements. It minimizes costly clean-up time and labor by making complete removal an uncomplicated one-product operation. ATR-165 is simply sprayed, mopped or wiped on the surface, allowed to penetrate and dissolve the solid deposit and washed off with mild, emulsifying detergent solutions, and clean water.

Uses & Directions



Use ATR-165 on heavy road-working vehicles such as asphalt spreaders, graders, oilers and dump trucks are economically de-tarred without harm to the protective finish. ATR-165 can also be used to clean pitch mops, buckets, picks and shovels. Tank wash operations can also use this product to soften modern polymeric adhesive materials.

Test on an inconspicuous area before using on painted surfaces. Use as is. Do not dilute with diesel, as it will diminish ATR-165's ability to solubilize the tar and adhesives. Use hot water for rinsing whenever possible.

ATR-165 can also be used to clean pitch mops, buckets, picks and shovels.

Health Hazard Summary



Vapors can cause nausea, dizziness, nausea, stupor, vomiting, headache, and/or irritation to nose, throat, and respiratory system. Causes irritation to eyes. Prolonged exposure may irritate skin.

Specifications



Appearance	clear, pale amber
Penetration	excellent
Rinsability	moderate
Corrosion	nil
Stability	very good
Free acid	none
Free alkali	none
Flash point.....	145°F
Specific gravity	0.930
Density	7.75 lbs./gal.

Package & Handling



55 gal drum JBC7251

SDS



HMIS	
HEALTH	2
FLAMMABILITY	2
PHYSICAL HAZARD	0
PERSONAL PROTECTION	X