




ATR-220

Asphalt & Tar Remover



Product Description

ATR-220 is specifically compounded to quickly clean vehicles and equipment exposed to tar, asphalt, bitumen, oil, grease, sludge and asphalt-based plastic cements. It minimizes costly clean-up time and labor by making complete removal an uncomplicated one-product operation. The concentrate is simply sprayed, mopped or wiped on the surface, allowed to penetrate and dissolve the soiled deposit and hosed clean with water. Heaviest build-ups are broken down and floated away by the special solvents and emulsifiers with minimum effort.



Uses & Directions

Use ATR-220 to clean heavy road working vehicles such as asphalt spreaders, graders, oilers and dump trucks are economically de-tarred without harm to the protective finish. Oil and petroleum companies will find this product indispensable for cleaning tank cars, transport and delivery trucks and storage areas.

Test on an inconspicuous area before using on painted surfaces. Use as is. Do not dilute with water, as it will diminish ATR-220's ability to solubilize the tar. Use water for rinsing off only.

ATR-220 can also be used to clean pitch mops, buckets, picks and shovels.



Health Hazard Summary

Vapors can cause nausea, dizziness, nausea, stupor, vomiting, headache, and/or irritation to nose, throat, and respiratory system. Causes irritation to eyes. Prolonged exposure may irritate skin.



Specifications

Appearanceclear, pale amber
Penetration excellent
Rinsability excellent
Corrosion nil
Stabilityvery good
Free acid none
Free alkali none
Flash point 145°F
Specific gravity 0.930
Density 7.75 lbs./gal.



Package & Handling

55 gal drum JCRE6007
6 gal pail JCRE6837

SDS



HMIS	
HEALTH	2
FLAMMABILITY	2
PHYSICAL HAZARD	0
PERSONAL PROTECTION	X