

Product Description



FOAM-X is a water dilutable, concentrated industrial strength silicone emulsion designed to control foam in a wide variety of applications. FOAM-X works effectively in very low concentrations, even in extreme pH conditions. Contains a preservative to guard against microbial growth.

Uses & Directions



FOAM-X is great for Refineries, Chemical Plants, Resin Manufacturing, Textiles, Agrochemicals, Printing Fountain Solutions, Tank Wash Operations, Disposal Plants, Municipalities, Treatment Tanks, and Sewage Treatment Plants to kill unwanted or nuisance foam quickly, efficiently, and permanently. For process applications, the operator must determine the concentration of FOAM-X based on the need at the time it is to be dispensed. One to 100 parts of active silicone per million parts foamer are sufficient to eliminate most foams.

In carpet extractors, steam cleaners, and automatic floor scrubbers, use 1 oz. per 10 gallons of expected recovery water. Begin by pre-diluting the Foam-X into a quart of water, and place it in the recovery tank.



Health Hazard Summary

Causes irritation to eyes. Prolonged exposure may irritate skin. May cause gastrointestinal disconfort, including nausea, vomiting, diarrhea, etc if ingested.

Specifications

Appearance Milky white Odor	
Specific Gravity	
рН	7-8
Percent Active	
Emulsifier Type	Nonionic
Flammability	Non-flammable
Dilution with effluent	> 1000 to 1
Evaporation rate	Very low
VOC's	None
Solubility in water	Complete
Biodegradable	
Storage Stability	
USDA Registered?	

* 1 year

Exempt from tolerance at 40 CFR 180.1001 (d) for pesticide formulations - applied to growing crops only

Package & Handling



275 gallon tote 55 gallon drum

NOT

JCRE24854 **JCRE4410**



john-henry.com tankwashsolutions.com pressurezone.com



800 Central Ave. Jefferson, LA 70121 (504) 888-8989

HMIS

1

0

0

В

HEALTH

FLAMMABILITY

PHYSICAL HAZARD PERSONAL PROTECTION

