




POWERFUL • CLEANING • SOLUTIONS

OXY-BLAST

Mildew Remover

Product Description



OXY-BLAST, activated hydrogen peroxide based cleaner, is designed to remove mildew stains and mold stains from ceramic, wood, fiberglass, metal, and other surfaces not harmed by water alone in areas affected by floods and high water. OXY-BLAST removes mildew stains as effectively as chlorine bleach, but without the odor or the damaging alkalinity, and provides a long term cleaning effect. In addition, OXY BLAST deodorizes and destroys the musty mold and mildew odors, leaving the air fresh and clean. OXY-BLAST may also be used as a cleaner and no-rinse final treatment in food processing and preparation areas, reefers, cold storage areas that are down for repairs, and the like. OXY-BLAST meets the requirements of 21 CFR 178.1005 for use on and around food processing equipment. Mildew stains and odors are a thing of the past with OXY-BLAST!

Uses & Directions



OXY-BLAST should be used undiluted for heavy duty cleaning, mold and mildew removal, and for residual action. The use of an automated spraying device is highly recommended, but not mandatory.

DIRECTIONS - For post treatment after a flood, rinse or pressure wash debris, mud, and all related residues. Surfaces should be "almost" dry when applying. Use undiluted via pump sprayer, and spray everything including stringers, studs, floors, inside return-air chambers, etc. Allow to air-dry. Do not rinse off.

Health Hazard Summary



Causes serious eye irritation. Causes skin irritation. Harmful if swallowed. May intensify fire; oxidizer. May cause respiratory irritation.

Specifications



Appearance..... Clear water white liquid
Odor..... None
Specific Gravity..... 1.0
pH..... 2.5 - 3.5
Flammability..... Non-flammable
Dilution - Daily Use..... Up to 128:1
Dilution - Flood Restoration..... Undiluted
Foam..... Low
Hardwater Tolerance..... Excellent
Solubility in water..... Complete
Butyl..... None
Phosphate..... None
Storage Stability..... Excellent

Estimated Usage: One Gal per 100 Sq Ft of house for complete gut/ pack-out. One Gal per 200 Sq Ft of house when only the first 4 feet of sheet-rock is replaced.

Daily Mopping: Use 1 oz. per gallon of water
General Cleaning: Use 2 oz. per gallon of water.

Package & Handling



55 gallon drum
6 gallon pail

JBC7768
JBC25236

SDS



HMIS	
HEALTH	2
FLAMMABILITY	0
PHYSICAL HAZARD	0
PERSONAL PROTECTION	X