



## **ROTO-WASH**

## Premium Aircraft Cleaner

Roto-Wash is formulated to remove exhaust deposits, light oils, bug residues, and all other naturally forming film deposits from the painted or bare aluminum surfaces of airplanes and helicopters. This product works in hot or cold water and rinses freely leaving no soap scum, even on aircraft with salt and other built-up soap residues. The materials used have been selected for their extremely low surface tension and their ability to penetrate quickly. Roto-Wash will not harm pressure washing equipment, and contains no phosphates, dyes, perfumes, or thickeners. All surfactants are biodegradable.

Use Roto-Wash to clean all types of aircraft, as well as support vehicles such as fuel trucks, buses, luggage carts, jetways, etc.

For light film, apply Roto-Wash at a 25 to 1 dilution ratio. For heavy films and/or oxidation (seldom washed aircraft), apply at 5 to 1. For heavy soot and oil soils, use straight. Using a downstream injector or under full pressure from a pressure washer, apply Roto-Wash from bottom to top, and allow to stand for at least 30 seconds before rinsing. Rinse first from bottom to top, and then from top to bottom. Hot water is desirable but not required. Wash areas small enough so as not to allow the product to dry before rinsing.

## SPECIFICATIONS FOR ROTO-WASH

clear, amber liquid
. 13.2±.5
1.00
None
Up to 25:1 with water
Moderate
Excellent
None
None
. None
Excellent, indefinite
No



